



KARSTEN TENTEN
SINDS 1981



Karsten **Touring** Awning

Specifications	
Set-up time	5 minutes
Depth	230 cm
Front height	230 cm
Canvas weight	3,4 kg
Weight of frame	2,2 kg
Material	100% Ten Cate cotton
Frame	Pre-curved aluminium
Frame diameter	26 mm
Colour	Beige, light grey or anthracite
Optional	Interchangeable side walls
Includes	Awning, arch pole, ridge pole, fix-on block, guy lines + peg set for both awning and optional side walls. Sturdy carry bag and setup instructions.

Karsten Touring	250	275	300	325	350	400
Keder length (cm)	250	275	300	325	350	400
Awning (kg)	3.3	3.5	3.5	3.6	3.6	3.8
Frame (kg)	2.0	2.2	3.3	3.4	3.6	3.9
Total*	6.8	7.2	8.4	8.5	8.7	9.2

**Total = including peg bag of 1.5 kg. measurements may slightly vary*

Sizing

To determine which Touring fits your camper(van) perfectly, first measure the horizontal part of the beading rail. Then choose the Touring closest to that length. For example, if your beading rail is 310 cm, opt for the Touring 300. If it's 380 cm, choose the Touring 400.

Information and prices

For more information and pricing on our awnings, scan the QR code:



made in
HOLLAND



Interchangeable **Side Walls**

Specifications	
Attachment	Via YKK zipper
Material	Ten Cate KD38 cotton 310 g/m ²
Colour	Beige, light grey or anthracite
Weight	Approx. 1.8 to 2 kg per piece
Options	With or without window

Afmetingen	
Zijwand A:	190 cm for rail height 180 to 200 cm
Zijwand B:	210 cm for rail height to 220 cm
Zijwand C:	230 cm for rail height to 240 cm
Zijwand D:	248 cm for rail height to 260 cm

Choosing a side wall

Measure the height of the keder rail on your caravan or camper (van) to determine the correct side wall. For a keder rail height of 200 cm, we recommend Side Wall B. At 220 cm, choose Side Wall C, and at 240 cm, Side Wall D.

How to measure:

